



Sealant and Primer Coverage Charts

Sealant Coverage Chart								
10.3 fl. oz. cartridge (18.6 cu.in.)								
Depth	Width							
	1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
1/8"	99	49.5	33	24.5	20	16.5	14	12.5
1/4"		24.5	20	12.5	10	8	7	6
3/8"			11	8	6.5	5.5	4.5	4
1/2"				6	5	4	3.5	3
<i>*All usages are linear feet per 10.3 oz. cartridge.</i>								
30 fl. oz. cartridge (54.2 cu.in.)								
Depth	Width							
	1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
1/8"	287	144	96	72	58	48	41	36
1/4"		72	48	36	28.5	24	20.5	18
3/8"			32	24	19.25	16	13.5	12
1/2"				18	16.25	12	10.25	9
<i>*All usages are linear feet per 30 oz. cartridge.</i>								
1-1/2 gallon unit (346.5 cu.in.)								
Depth	Width							
	1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
1/8"	1848	924	615	462	369	308	264	231
1/4"		412	308	231	185	153	132	116
3/8"			204	153	123	102	87	77
1/2"				116	92	77	66	57
<i>*All usages are linear feet per 1-1/2 gallon unit.</i>								
2 gallon pail (462 cu.in.)								
Depth	Width							
	1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
1/8"	2464	1236	820	616	492	410	352	308
1/4"		616	410	308	246	204	176	154
3/8"			276	204	164	136	116	102
1/2"				154	122	102	88	76
<i>*All usages are linear feet per 2 gallon pail.</i>								
5 gallon pail (1155 cu.in.)								
Depth	Width							
	1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
1/8"	6160	3080	2050	1540	1230	1025	880	770
1/4"		1540	1025	770	565	510	440	380
3/8"			680	510	410	340	290	255
1/2"				385	305	255	220	190
<i>*All usages are linear feet per 5 gallon pail.</i>								

Primer Coverage Chart*			
Gallons of Sealant	Primer Required		
	Pints	Quarts	Gallons
4	1	-	-
8	2	1	-
12	3	-	-
16	4	2	-
20	5	-	-
24	6	3	-
28	7	-	-
32	8	4	1
36	9	-	-
40	10	5	-
44	11	-	-
48	12	6	-
52	13	-	-
56	14	7	-
60	15	-	-
64	16	8	2
68	17	-	-
72	18	9	-
76	19	-	-
80	20	10	-
84	21	-	-
88	22	11	-
92	23	-	-
96	24	12	3
100	25	-	-
104	26	13	-
<i>*One quart of primer will cover 1200 linear feet, two sides of a 1/2" deep joint. Primer coverage varies depending on the porosity of the substrate.</i>			

Additional information

Polymeric Systems, Inc. is a leading manufacturer of adhesives and sealants.

PSI is a part of Whitford Worldwide. Please see reverse side for address and contact information for Polymeric Systems and PSI's European representative at Whitford Plastics Ltd.

For more information contact Polymeric Systems at:

Polymeric Systems, Inc.
47 Park Avenue
Elverson, PA, USA 19520
800-CAULK IT (800-228-5548)
Tel: [1] 610-286-2500
Email: sales@polymericsystems.com
Website: polymericsystems.com

In the EU contact:

Whitford Plastics Ltd.
10, Christleton Court, Manor Park
Runcorn, Cheshire, UK WA7 1ST
Tel: [44] (1928) 571000
Email: sales@whitfordww.co.uk
Website: whitfordww.com

NON-WARRANTY: ALL RECOMMENDATIONS, STATEMENTS AND TECHNICAL DATA CONTAINED HEREIN ARE BASED ON TESTS WE BELIEVE TO BE RELIABLE AND CORRECT, BUT ACCURACY AND COMPLETENESS OF SAID TESTS ARE NOT GUARANTEED AND ARE NOT TO BE CONSTRUED AS A WARRANTY, EITHER EXPRESS OR IMPLIED. USER SHALL RELY ON HIS OWN INFORMATION AND TESTS TO DETERMINE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY RESULTING FROM THIS USE OF THE PRODUCT. MANUFACTURER'S SOLE RESPONSIBILITY SHALL BE TO REPLACE THAT PORTION OF THE PRODUCT OF THE MANUFACTURER THAT PROVES TO BE DEFECTIVE. MANUFACTURER SHALL NOT BE LIABLE TO THE BUYER OR ANY THIRD PARTY FOR INJURY, LOSS OR DAMAGE DIRECTLY OR INDIRECTLY RESULTING FROM USE OF, OR INABILITY TO USE, THE PRODUCT. RECOMMENDATIONS OR STATEMENTS OTHER THAN THOSE CONTAINED IN A WRITTEN AGREEMENT SIGNED BY AN OFFICER OF THE MANUFACTURER SHALL NOT BE BINDING UPON THE MANUFACTURER.

Form No. 3006-EM07